GARE 16

Material Safety Data Sheet
May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910 1200. Standard must be consulted for specific requirements.

Hazardous Components (Specific Chemical Identity, Common Name(s))

U.S. Department of Labor

Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072

ACGIH TLV

IDENTITY (as Used on Label and List)	Note: Blank spaces are not permitted.
Gare SY-Texture Powder (SY-4420)	applicable or no information is a
Gale 31-16xtule Fuwdel (31-4420)	must be marked to indicate that

If any item is not vailable, the space

Recommended

% (optional)

Section I	
Manufacturer's name	Emergency Telephone Number
Gare Inc.	Regional Poison Control Center (Poisondex System)
Address (Number, Street, City, State and ZIP Code)	Telephone Number for Information 978-373-9131
165 Rosemont Street	Date Prepared November 2004
Haverhill, MA 01831	Signature of Preparer (optional)
Section II—Hazardous Ingredients/Identity Informatio	n
	Other Limits

OSHA PEL



This material has been evaluate	ed under the provision o	of LHAMA (Labeling of Haza	rdous Art Mater	ials Act)	
and California Proposition 65 by	y a board certified toxico	ologist. This product was jud	ged to be non-t	oxic and	
non-flammable under the propo	sed use conditions. No	special warning label is requ	uired under the	provision	
of LHAMA or California Proposi	tion 65. The label shoul	ld state, "Conforms to ASTM	I D 4236"		
Section III—Physical/Chemical C	haracteristics				
Boiling Point N/A	N/A	Specific Gravity (H ₂ 0 = 1)	Specific Gravity (H ₂ 0 = 1)		
Vapor Pressure (mm Hg)	N/A	Melting Point	Melting Point		
Vapor Density (AIR = 1)	N/A	Evaporation Rate (Butyl A	Evaporation Rate (Butyl Acetate = 1)		
Solubility in Water essentially ins		<u> </u>		l	
Appearance and Odor White power	der, no odor.				
Section IV—Fire and Explosion I	lazard Data				
Flash Point (Method Used) Will not burn		Flammable Limits N/A	LEL N/A	UEL N/A	
Extinguishing Media Not combustil	ble.		4	-	
Special Fire Fighting Procedures none)				
Unusual Fire and Explosion Hazards	one				

(Reproduce locally) OSHA 174 Sept. 1985

Section V—	-Reactivity Data				
Stability		Unstable		Conditions to Av	^{oid} N/A
		Stable	х		
Incompatibility	(Materials to Avoid)	eacts with acid to lib	erate carbon o	lioxide gas.	
Hazardous De	ecomposition or Byprodu	icts N/A		<u>_</u>	
Hazardous		May Occur		Conditions to Av	oid N/A
Polymerizatio	n	Will Not Occur	•		
041 1/1	U14- UI B-4-		Х		
Route(s) of E	-Health Hazard Data	- Intertelline	Ski	n?	Ingestion?
		Non-toxic			
- Ticalui i lazan	ds (Acute and Chronic)	Non-toxic			
Carcinogenici	tv	NTP?	IAF	RC Monographs?	OSHA Regulated?
	Not suspected				
Signs and Sv	mptoms of Exposure N/				
	· · N/.	Α			
Medical Cond	itions				
		Mechanically abrasiv	ve to the eye.	Overexposure mag	y cause some skin dryness.
Emergency a	nd First Aid Procedures	Eye contact: Flush w	vith water for 1	l5 minutes.	
		contact: Wash with			
		fe Handling and Use			
Steps to Be 1	aken in Case Material Is	Clea	an up with pap	er towels and spo	nge.
Waste Dispos	al Method				
	Dispose	e of paper towels in t	trash and was	h out sponge.	
Precautions to	Be Taken in Handling a	and Storing			
	be raken in rianding t	- Keep bott		erly tightened.	
Other Precau	tions	Do not make du	ust.		
	N/A				
Section VIII	—Control Measures				
		Not for spray applic	-4!		
Ventilation	Local Exhaust N/A	Not for spray applic	ation.	Special N/A	
	Mechanical (General)			Other	
Protective Cla	condinical (Coneral)	N/A	E.,,	Other N/A	
Other Desired	Only if irritatio	n occurs	Eye	Protection Avoid ey	e contact
Otner Protect	ve Clotning or Equipmen	Twear apron or smo	ock		
Work/Hygienic Practices Maintain personal and work area cleanliness					