GARE 23

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910 1200. Standard must be consulted for specific requirements.

Hazardous Components (Specific Chemical Identity, Common Name(s))

U.S. Department of Labor

Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072

ACGIH TLV

Other Limits

Recommended

% (optional)

Carra Irra	Deviand Deigen Control Conten (Deigender Creters)
Manufacturer's name	Emergency Telephone Number
Section I	
Stains. PS, CPS, GCPS, 6100 Series	must be marked to indicate that.
Gare Pearl, Cultured Pearl, and Golden Cultured Pearl	applicable or no information is available, the space
IDENTITY (as Used on Label and List)	Note: Blank spaces are not permitted. If any item is not

Manufacturer's name	Emergency Telephone Number
Gare Inc.	Regional Poison Control Center (Poisondex System)
Address (Number, Street, City, State and ZIP Code)	Telephone Number for Information 978-373-9131
165 Rosemont Street	Date Prepared November 2004
Haverhill, MA 01831	Signature of Preparer (optional)

This material has been evaluated under the provision of LHAMA (Labeling of Hazardous Art Materials Act)

OSHA PEL



and California Proposition 65 by a board	certified toxicologist	. This product was judg	ged to be non-toxic	and	
non-flammable under the proposed use c	onditions. No specia	al warning label is requ	ired under the provi	ision	
of LHAMA or California Proposition 65. TI	ne label should state	e, "Conforms to ASTM	D 4236"		
Section III—Physical/Chemical Characterist	ics				
Boiling Point Water	212° F	Specific Gravity (H ₂ 0 = 1)		1.1	
Vapor Pressure (mm Hg)	N/A	Melting Point		N/A	
Vapor Density (AIR = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)		As water	
Solubility in Water Essentially insoluble					
Appearance and Odor Colored acrylic paint	, mild odor.				
Section IV—Fire and Explosion Hazard Data	3				
Flash Point (Method Used) Will not burn		Flammable Limits N/A	LEL N/A	UEL N/A	
Extinguishing Media Not combustible. This i	s a water-based pi	oduct.			
Special Fire Fighting Procedures None					
Unusual Fire and Explosion Hazards None					

(Reproduce locally) OSHA 174 Sept. 1985

Section V—	-Reactivity Data					
Stability		Unstable			Conditions to Avoid N/	/A
		Stable	х			
Incompatibility	(Materials to Avoid) No	one known			l	
Hazardous De	ecomposition or Byprodu	icts N/A				
Hazardous		May Occur			Conditions to Avoid N/	/A
Polymerizatio	n	Will Not Occur				
041 1/1			X			
Route(s) of E	-Health Hazard Data			Skin?		Ingestion?
		Inhalation? Non-toxic	<u> </u>			
- I lealth i lazan	ds (Acute and Chronic)	Non-toxic				
Carcinogenici	tv	NTP?		IARC Mo	onographs?	OSHA Regulated?
	ty not suspected					
Signs and Sv	mptoms of Exposure N/					
	N/	Α				
Medical Cond	itions					
		echanically abrasiv	e to the eye.	Overe	exposure may caus	se some skin dryness.
Emergency a	nd First Aid Procedures	Eye contact: Flush	with water fo	or 15 m	ninutes	
		contact: Wash with				
		afe Handling and Use				
Steps to Be T	aken in Case Material Is	Released or Spilled Cle	an up with p	aper t	owels and sponge.	
Wests Dispes	al Mathad					
Waste Dispos	Dispose	e of paper towels in	trash and w	ash oเ	ıt sponges.	
Droggutions to	. Do Tokon in Handling	and Storing				
Precautions to	Be Taken in Handling a	Keep bot	tle covers pi	roperly	tightened.	
Other Dressu	liana					
Other Precau	N/A					
	—Control Measures					
	Least Exhaust	Not for spray applic	cation.		Chariel	
Ventilation	Local Exhaust N/A				Special N/A	
	Mechanical (General)	N/A			Other N/A	
Protective Glo	Oves Only if irritatio	n occurs		Eye Prof	ection Avoid eye co	ntact
Other Protect	ive Clothing or Equipmer	^{nt} Wear apron or sm	ock			
Work/Hygieni	c Practices Maintain	personal and work	area cleanlin	ess		