

GARE 51

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910 1200. Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (as Used on Label and List)

Gare Thick-N-Etch SY-4432

Note: Blank spaces are not permitted. If any item is not applicable or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's name

Gare Inc.

Address (Number, Street, City, State and ZIP Code)

165 Rosemont Street

Haverhill, MA 01831

Emergency Telephone Number

Regional Poison Control Center (Poisondex System)

Telephone Number for Information **978-373-9131**

Date Prepared **November 2004**

Signature of Preparer (optional)

Section II—Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Name(s))

OSHA PEL

ACGIH TLV

Other Limits
Recommended

% (optional)

NON-TOXIC

CONFORMS TO
ASTM D 4236

This material has been evaluated under the provision of LHAMA (Labeling of Hazardous Art Materials Act) and California Proposition 65 by a board certified toxicologist. This product was judged to be non-toxic and non-flammable under the proposed use conditions. No special warning label is required under the provision of LHAMA or California Proposition 65. The label should state, "Conforms to ASTM D 4236"

Section III—Physical/Chemical Characteristics

Boiling Point	Water	212°F	Specific Gravity (H ₂ O = 1)	1.2
Vapor Pressure (mm Hg)		N/A	Melting Point	N/A
Vapor Density (AIR = 1)		N/A	Evaporation Rate (Butyl Acetate = 1)	As water

Solubility in Water **In solution**

Appearance and Odor **Clear liquid, practically odorless.**

Section IV—Fire and Explosion Hazard Data

Flash Point (Method Used)	Will not burn.	Flammable Limits	N/A	LEL	N/A	UEL	N/A
---------------------------	-----------------------	------------------	------------	-----	------------	-----	------------

Extinguishing Media **Not combustible. This is a water based product.**

Special Fire Fighting Procedures **None**

Unusual Fire and Explosion Hazards **None**

(Reproduce locally)

OSHA 174 Sept. 1985

Section V—Reactivity Data

Stability	Unstable		Conditions to Avoid N/A
	Stable	x	
Incompatibility (<i>Materials to Avoid</i>) None known			
Hazardous Decomposition or Byproducts N/A			
Hazardous Polymerization	May Occur		Conditions to Avoid N/A
	Will Not Occur	x	

Section VI—Health Hazard Data

Route(s) of Entry	Inhalation? N/A	Skin? yes	Ingestion? N/A
Health Hazards (<i>Acute and Chronic</i>) Prolonged contact may cause eye or skin irritation.			
Carcinogenicity Not suspected	NTP?	IARC Monographs?	OSHA Regulated?
Signs and Symptoms of Exposure Irritation at contact point.			
Medical Conditions Generally Aggravated by Exposure None known			
Emergency and First Aid Procedures Eye contact: Flush with water 15 minutes. If irritation persists, see a physician. Skin contact: Wash with soap and water.			

Section VII—Precautions for Safe Handling and Use

Steps to Be Taken in Case Material Is Released or Spilled	Clean up with paper towels and sponge.
Waste Disposal Method	Dispose of paper towels in trash and wash out sponge.
Precautions to Be Taken in Handling and Storing	Keep bottle covers properly tightened. Keep out of reach of children.
Other Precautions	When using do not eat, drink or smoke. Wash hands immediately after use.

Section VIII—Control Measures

Respiratory Protection (<i>Specify Type</i>)	Not for spray application.		
Ventilation	Local Exhaust N/A	Special	N/A
	Mechanical (<i>General</i>) N/A	Other	N/A
Protective Gloves	If irritation occurs.	Eye Protection	Avoid eye contact.
Other Protective Clothing or Equipment	Wear apron or smock.		
Work/Hygienic Practices	Maintain personal and work area cleanliness.		