



# MATERIAL SAFETY DATA SHEET

01326 100126 604

## SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

### CHEMICAL PRODUCT IDENTIFICATION:

PRODUCT CODE . . . : 01326 100126 604  
 PRODUCT NAME . . . : Clear Gloss 2000 **CLEAR GLOSS SPRAY**  
 PRODUCT CLASS . . . : Aerosol Coating

MSDS PREPARATION DATE : 09/24/2004

### MANUFACTURER IDENTIFICATION:

RAABE CORPORATION  
 PO BOX 1090  
 MENOMONEE FALLS WI 53052

### CUSTOMER IDENTIFICATION:

**GARE**  
**165 ROSEMONT ST.**  
**HAVERHILL, MA 01831**

### EMERGENCY TELEPHONE NUMBERS:

24 HOURS A DAY - CALL CHEMTREC : 800-424-9300  
 INTERNATIONAL CALLS TO CHEMTREC : 703-527-3887  
 8 AM TO 4:30 PM CENTRAL TIME : 262-255-9500

## SECTION 2 - COMPOSITION, INFORMATION ON INGREDIENTS

### 1 N-BUTANE

CAS# 106-97-8

#### N-BUTANE

PCT BY WT: 12.0000 VAPOR PRESSURE: 879.100 MMHG @ 68F LEL 1.80

#### EXPOSURE LIMIT:

ACGIH TLV-TWA 800 ppm  
 ACGIH TLV-STEL NO INFO  
 OSHA PEL-TWA 800 ppm  
 COMPANY N.E.

### 2 PROPANE

CAS# 74-98-6

#### PROPANE

PCT BY WT: 16.0000 VAPOR PRESSURE: 5585.200 MMHG @ 68F LEL 2.20

#### EXPOSURE LIMIT:

ACGIH TLV-TWA 1000 ppm  
 ACGIH TLV-STEL NO INFORMATION

### 3 ACETONE

CAS# 67-64-1

01326 100126 604

#### ACETONE



# MATERIAL SAFETY DATA SHEET

PCT BY WT: 26.0000 VAPOR PRESSURE: 231.000 MMHG @ 68F LEL 2.60

EXPOSURE LIMIT:

ACGIH TLV-TWA	750 ppm
ACGIH TLV-STEL	1000 ppm
OSHA PEL-TWA	750 ppm
OSHA PEL-STEL	1000 ppm
COMPANY	N.E.

4 GLYCOL ETHER PM ACETATE

CAS# 108-65-6

PROPYLENE GLYCOL METHYL ETHER ACETATE

PCT BY WT: 15.0000 VAPOR PRESSURE: 3.700 MMHG @ 68F LEL 1.30

EXPOSURE LIMIT:

ACGIH TLV-TWA	NOT ESTABLISHED
ACGIH TLV-STEL	NOT ESTABLISHED

5 TOLUENE

CAS# 108-88-3

TOLUENE

PCT BY WT: 20.0000 VAPOR PRESSURE: 38.000 MMHG @ 68F LEL 1.40

EXPOSURE LIMIT:

ACGIH TLV-TWA	50 ppm
ACGIH TLV-STEL	NO INFO
OSHA PEL-TWA	50 ppm
COMPANY	N.E.
OTHER	CALIFORNIA PROP 65 (1/01/91)

\*\*\*\*\*  
 This substance is classified as a hazardous air pollutant.  
 \*\*\*\*\*

\*\*\*\*\*  
 This product contains no reported carcinogens or suspected  
 carcinogens.  
 \*\*\*\*\*

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

Harmful if swallowed.  
 Harmful if inhaled.  
 Causes eye irritation.  
 Causes skin irritation.  
 Vapors irritating to eyes and respiratory tract.  
 Extremely flammable liquid and vapor.  
 Vapors may cause flash fire or explosion.  
 Extremely flammable aerosol.

RAABE CORPORATION

N92 W14701 Anthony Avenue  
 Menomonee Falls, WI 53051-1630  
 P.O. Box 1090 Menomonee Falls, WI 53052-1090  
 800 966 7580 | 262 255 9500 | fax 262 255 0684  
 www.raabecorp.com



# MATERIAL SAFETY DATA SHEET

PAGE 3

01326 100126 604

---

Contents under pressure.

**EYE:**

Exposure to liquid or vapor may cause eye irritation. Symptoms may include burning, tearing, redness, and swelling.

**SKIN:**

May cause skin irritation.

Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

**INHALATION:**

Exposure to high concentrations of vapors may cause dizziness, breathing difficulty, headaches or respiratory irritation.

Extremely high concentrations may cause drowsiness, staggering, confusion, unconsciousness, coma or death.

Intentional misuse by deliberately concentrating and inhaling the contents of this product can be harmful or fatal.

**INGESTION:**

Moderately toxic. May cause stomach discomfort, nausea, vomiting, diarrhea, and narcosis.

**CHRONIC EFFECTS:**

Chronic overexposure to a component or components in this material has been found to cause the following effects in laboratory animals:

- Kidney damage
- Eye damage
- Lung damage
- Liver damage
- Spleen damage
- Brain damage

Chronic overexposure to a component or components in this product has been suggested as a cause of the following effects in humans:

- Liver damage

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Product contains toluene which may be harmful to the fetus based on animal studies.

Repeated exposure to toluene has been associated with high frequency hearing loss in laboratory animals. The human consequences of this finding is uncertain.

---

## SECTION 4 - FIRST AID MEASURES

---

**EYE CONTACT:**

Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

**SKIN CONTACT:**

Wash thoroughly with soap and water and seek medical attention if irritation persists. Remove contaminated clothing. Launder contaminated



# MATERIAL SAFETY DATA SHEET

clothing before reuse.

INHALATION:

01326 100126 604

For inhalation overexposure move person to fresh air. If breathing stops, apply artificial respiration and seek medical attention.

INGESTION:

Since this product may contain materials which can cause lung damage if aspirated into the lungs, the decision whether to induce vomiting or not must be made by a physician after careful consideration of all materials ingested.

NOTE TO PHYSICIAN:

SECTION 5 - FIRE FIGHTING MEASURES

FIRE AND EXPLOSIVE PROPERTIES OF THE PRODUCT:

Flashpoint . . . . .	: Less Than -25 °F
Explosion Level . . . . .	: Low (LEL) - 1.3
	High (UEL)- 13.1

EXTINGUISHING MEDIA:

Use Dry Chemical, Carbon Dioxide or Chemical Foam.

FIRE-FIGHTING PROCEDURES AND EQUIPMENT:

Contents under pressure. Do not use or store near sources of heat, sparks or open flame. Keep away from any source of heat such as sunlight, heaters or stoves that could cause the container to burst. Do not puncture or incinerate. Do not crush or place in a garbage compactor. Do not store above 120 degrees F. Aerosol containers may explode when exposed to extreme heat.

Product vapors are heavier than air and may travel a long distance to a source of ignition and flash back.

Full protective equipment including self-contained breathing apparatus to avoid inhalation of vapors should be used.

Water spray should not be used except to keep down vapors or cool closed containers to prevent build-up of pressure. If water is used, fog nozzles are preferred.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

CLEAN-UP AND CONTAINMENT:

Remove all sources of ignition. Avoid heat, sparks, flames and anything which could cause fire.

Ventilate area of spill and adjacent low lying areas. Avoid breathing solvent vapors. Remove with inert absorbent materials and non-sparking tools.

SECTION 7 - HANDLING AND STORAGE



# MATERIAL SAFETY DATA SHEET

HANDLING:

Wash hands thoroughly after handling.

STORAGE:

Store in a cool dry area with ventilation suitable for storing materials

01326 100126 604

shown in section 2.

Keep away from heat, sparks and flame.

Store in a cool place away from direct sunlight or any source of ignition. Do not store at temperatures above 120 degrees F.

### SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

ENGINEERING CONTROLS:

Sufficient ventilation, in volume and pattern, should be provided to keep air contamination below current applicable OSHA permissible exposure limit or ACGIH's TLV limit.

RESPIRATORY PROTECTION:

If workplace exposure limits are exceeded for any component(see section 2 for hazardous components and exposure limits), a NIOSH/OSHA approved respirator suitable for components listed is recommended.

SKIN PROTECTION:

Chemical resistant plastic or rubber gloves recommended for prolonged or repeated contact.

EYE PROTECTION:

Chemical goggles with side shields or face shield recommended if contact with the eyes is likely.

OTHER PROTECTIVE EQUIPMENT:

Appropriate impervious clothing is recommended if prolonged or repeated contact is likely.

HYGIENIC PRACTICES:

Wash hands before eating or smoking. Smoke in designated areas only.

### SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Vapor Pressure . . . . .	:	5585.20	mm Hg @ 20 C
Vapor Density . . . . .	:	-N/A	
Boiling Range . . . . .	:	Lower - 1.0	°F
		Higher - 302.0	°F
Specific Gravity . . . . .	:	.744	
Formula Weight per Volume . . . . .	:	6.1916	LB/GL
VOC (Calculated, LB/GAL) . . . . .	:	5.145	
VOC (Calculated, GM/L). . . . .	:	616.52	
Percent Volatile by Weight. . . . .	:	90.1961	
Percent Volatile by Volume . . . . .	:	93.2837	



# MATERIAL SAFETY DATA SHEET

Evaporation Rate . . . . . : 7.700 (n-Butyl Acetate = 1)  
Viscosity . . . . . : -N/A

-----  
SECTION 10 - STABILITY AND REACTIVITY  
-----

CONDITIONS TO AVOID:

Avoid contact with heat, sparks, and open flame.  
Product may explode if heated. Keep cool, avoid exposure to heat.

INCOMPATIBILITIES:

-----  
01326 100126 604  
-----

Strong oxidizing agents.

DECOMPOSITION:

Thermal decomposition may produce carbon dioxide, carbon monoxide, and unidentifiable organic materials.

POLYMERIZATION:

No hazardous polymerization will occur under normal conditions.

STABILITY:

The product is stable under normal storage conditions.  
-----

SECTION 11 - TOXICOLOGICAL INFORMATION  
-----

No specific information is available. Please refer to Section 2 and 3 for available information on exposure limits and hazards identification.  
-----

SECTION 12 - ECOLOGICAL INFORMATION  
-----

No specific ecological information is available for this product.  
-----

SECTION 13 - DISPOSAL CONSIDERATIONS  
-----

WASTE DISPOSAL:

Place in closed containers. Dispose of product in accordance with local, county, state, and federal regulations.  
-----

SECTION 14 - TRANSPORT INFORMATION  
-----

Ground shipment of limited or excepted quantities of aerosols or liquid paint in containers of 1 quart or less:

CONSUMER COMMODITY, ORM-D

Ground shipment of liquid paint in containers more than 1 quart:

PAINT, FLAMMABLE LIQUID, UN1263, CLASS 3, GROUP II

(Regulatory sources: DOT 49CFR 172.101)

Air shipment of limited or excepted quantities of aerosols or liquid paint in containers of 1 quart or less:

CONSUMER COMMODITY, ID 8000, CLASS 9 MISCELLANEOUS LABEL



# MATERIAL SAFETY DATA SHEET

(Regulatory sources: ATAI Quantity Exemptions - Table 2.8.4, 2.7.A, 2.7.5, Packaging Instruction: 910)

OR

AEROSOLS, FLAMMABLE, UN1950, CLASS 2.1 LABEL

(Regulatory sources: ATAI Quantity Exemptions - Table 2.8.1, 2.8.4, Packaging Instruction: Y203)

-----  
SECTION 15 - REGULATORY INFORMATION  
-----

SARA 313 INFORMATION:

This product contains the following substances subject to the

-----  
01326 100126 604  
-----

reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

TOLUENE

CAS# 108-88-3 PCT BY WT: 20.1960  
-----

FEDERAL REGULATIONS:

TOXIC SUBSTANCES CONTROL ACT: The chemical substances in this product are listed on the TSCA Section 8 inventory.

STATE REGULATIONS:

This product contains chemical(s) which are listed on California's proposition 65 list. If the product is to be sold or used in California the following warning statement must appear on the label:

Warning! This product contains a chemical or chemicals known to the State of California to cause birth defects or other reproductive harm.

NEW JERSEY RIGHT-TO-KNOW

No non-hazardous ingredients are among the top five ingredients  
-----

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3 %

----- CHEMICAL NAME ----- CAS NUMBER  
Acrylic Polymer Not Listed  
-----

INTERNATIONAL REGULATIONS:

CANADA: The chemical substances in this product are listed on the Canadian Domestic Substances List.  
-----

SECTION 16 - OTHER INFORMATION  
-----

The information contained on this MSDS is believed to be reliable and accurate. Due to the changing nature of government information, it is impossible to guarantee the accuracy of the information contained herein. Since the conditions of handling and use are beyond our control, we make



# MATERIAL SAFETY DATA SHEET

no guarantee of results and assume no liability for damages incurred by the use of this material. This information should not be regarded as legal advice or regulation. It is the responsibility of the user to comply with all Federal, State, and Local laws and regulations. For questions relating to specific aspects of the requirements and regulations consult the proper regulatory agency.

HMIS RATINGS:

HEALTH: 2\* FLAMMABILITY: 3 REACTIVITY: 0 PERSONAL PROTECTION: X

Issued to . . . . . :  
Attention: . . . . . : Material Safety Data Sheet Coordinator  
The attached Material Safety Data Sheet relates potential hazards and recommended practices for safe handling of the product that you purchased from Raabe Corporation.  
We urge you and your employees to review the entire MSDS prior to handling, use or disposal of the product.  
You are required to keep this MSDS on file for reference by company employees or government regulatory officials.  
If you resell or distribute this product, you must furnish a copy of the MSDS to your customer.

01326 100132 604 01

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

CHEMICAL PRODUCT IDENTIFICATION:

PRODUCT CODE . . . . : 01326 100132 604  
PRODUCT NAME . . . . : WEATHER-ALL  
PRODUCT CLASS . . . . : Aerosol Product

MSDS PREPARATION DATE : 09/24/2004

MANUFACTURER IDENTIFICATION:

RAABE CORPORATION  
PO BOX 1090  
MENOMONEE FALLS WI 53052

CUSTOMER IDENTIFICATION:

EMERGENCY TELEPHONE NUMBERS:

24 HOURS A DAY - CALL CHEMTREC : 800-424-9300  
INTERNATIONAL CALLS TO CHEMTREC : 703-527-3887  
8 AM TO 4:30 PM CENTRAL TIME : 262-255-9500

SECTION 2 - COMPOSITION, INFORMATION ON INGREDIENTS

1 ETHYLBENZENE  
CAS# 100-41-4

ETHYLBENZENE

PCT BY WT: 3.7880 VAPOR PRESSURE: 19.000 MMHG @ 68F LEL 1.20

EXPOSURE LIMIT:

ACGIH TLV-TWA 100 ppm





# MATERIAL SAFETY DATA SHEET

PAGE 9

ACGIH TLV-STEL 125 ppm  
OSHA PEL-TWA 100 ppm  
OSHA PEL-STEL 125 ppm  
OTHER IARC (2B), CALIFORNIA PROP 65 (6/11/04)

---

## 2 METHYL N-AMYL KETONE

CAS# 110-43-0

METHYL N-AMYL KETONE

PCT BY WT: 3.0000 LEL 1.10

EXPOSURE LIMIT:

ACGIH TLV-TWA 50 ppm  
ACGIH TLV-STEL NO INFO  
OSHA PEL-TWA 50 ppm  
COMPANY N.E.

---

01326 100132 604 01

---

## 3 NAPHTHA

CAS# 8030-30-6

NAPHTHA

PCT BY WT: 12.0000 LEL 1.10

EXPOSURE LIMIT:

ACGIH TLV-TWA 400 ppm  
ACGIH TLV-STEL NO INFO

---

## 4 N-BUTANE

CAS# 106-97-8

N-BUTANE

PCT BY WT: 15.0000 VAPOR PRESSURE: 879.100 MMHG @ 68F LEL 1.80

EXPOSURE LIMIT:

ACGIH TLV-TWA 800 ppm  
ACGIH TLV-STEL NO INFO  
OSHA PEL-TWA 800 ppm  
COMPANY N.E.

---

## 5 N-HEXANE

CAS# 110-54-3

N-HEXANE

PCT BY WT: 10.0000 LEL 1.20

EXPOSURE LIMIT:

ACGIH TLV-TWA 50 ppm  
ACGIH TLV-STEL NO INFO  
OSHA PEL-TWA 50 ppm  
COMPANY N.E.

---

## 6 PROPANE



# MATERIAL SAFETY DATA SHEET

CAS# 74-98-6

PROPANE

PCT BY WT: 21.0000 VAPOR PRESSURE: 5585.200 MMHG @ 68F LEL 2.20

EXPOSURE LIMIT:

ACGIH TLV-TWA 1000 ppm  
ACGIH TLV-STEL NO INFORMATION

7 XYLENE

CAS# 1330-20-7

XYLENE

PCT BY WT: 21.0000 VAPOR PRESSURE: 6.600 MMHG @ 68F LEL 1.00

EXPOSURE LIMIT:

ACGIH TLV-TWA 100 ppm  
ACGIH TLV-STEL 150 ppm  
OSHA PEL-TWA 100 ppm  
OSHA PEL-STEL 150 ppm  
COMPANY N.E.  
LD50(ORAL) 4300 mg/kg

01326 100132 604 01

LD50(DERMAL) 1700 mg/kg  
LC50 18892 mg/m3

8 METHYL ETHYL KETONE

CAS# 78-93-3

METHYL ETHYL KETONE

PCT BY WT: 1.0000 VAPOR PRESSURE: 85.000 MMHG @ 68F LEL 1.80

EXPOSURE LIMIT:

ACGIH TLV-TWA 200 ppm  
ACGIH TLV-STEL 300 ppm  
OSHA PEL-TWA 200 ppm  
COMPANY N.E.

9 ISOBUTYL ACETATE

CAS# 110-19-0

ISOBUTYL ACETATE

PCT BY WT: 3.0000 LEL 1.30

EXPOSURE LIMIT:

ACGIH TLV-TWA 150 ppm  
ACGIH TLV-STEL NO INFO  
OSHA PEL-TWA 150 ppm  
COMPANY N.E.  
LD50(ORAL) 13400 mg/kg (Rat)  
LD50(DERMAL) >17400 mg/kg (Rabbit)  
LC50 >8000 ppm (Rat)



# MATERIAL SAFETY DATA SHEET

\*\*\*\*\*  
 This product contains one or more reported carcinogens or suspected carcinogens which are noted NTP, IARC, or OSHA-Z in the other limits recommended column.  
 \*\*\*\*\*

\*\*\*\*\*  
 This substance is classified as a hazardous air pollutant.  
 \*\*\*\*\*

-----  
 SECTION 3 - HAZARDS IDENTIFICATION  
 -----

EMERGENCY OVERVIEW:

- Harmful if inhaled.
- Causes eye irritation.
- Vapors irritating to eyes and respiratory tract.
- Extremely flammable liquid and vapor.
- Vapors may cause flash fire or explosion.
- Extremely flammable aerosol.
- Contents under pressure.

EYE:

May cause severe corneal injury if liquid comes in contact with the eyes.

-----  
 01326 100132 604 01  
 -----

SKIN:

- May cause skin irritation.
- Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).
- Skin contact may aggravate an existing dermatitis.

INHALATION:

- Exposure to high concentrations of vapors may cause dizziness, breathing difficulty, headaches or respiratory irritation.
- Extremely high concentrations may cause drowsiness, staggering, confusion, unconsciousness, coma or death.
- Excessive inhalation of vapors can cause nasal and respiratory irritation.
- Liquid or vapor may be irritating to skin, eyes, throat or lungs.
- Intentional misuse by deliberately concentrating and inhaling the contents of this product can be harmful or fatal.
- Pre-existing heart disorders may be aggravated by exposure to a component in this product.
- Persons with pre-existing, non-specific bronchial hyperreactivity can respond to concentrations below the TLV with symptoms as well as an asthma attack.

INGESTION:

Moderately toxic. May cause stomach discomfort, nausea, vomiting, diarrhea, and narcosis.



# MATERIAL SAFETY DATA SHEET

PAGE 12

Aspiration of material into the lungs if swallowed or if vomiting occurs can cause chemical pneumonitis which can be fatal.

## CHRONIC EFFECTS:

Chronic overexposure to a component or components in this material has been found to cause the following effects in laboratory animals:

- Kidney damage
- Eye damage
- Lung damage
- Liver damage
- Spleen damage
- Anemia
- Brain damage

Chronic overexposure to a component or components in this product has been suggested as a cause of the following effects in humans:

- Cardiac abnormalities
- Peripheral nerve damage
- Visual disturbances
- Cardiac arrhythmias

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Repeated breathing or skin contact of methyl ethyl ketone may increase the potency of neurotoxins such as hexane if exposures occur at the same time.

In February 2000 the International Agency for Research on Cancer (IARC) classified ethylbenzene as possibly carcinogenic to humans (Group 2B) on

---

01326 100132 604 01

---

the basis of sufficient evidence for carcinogenicity in experimental animals but inadequate evidence for cancer in humans.

---

## SECTION 4 - FIRST AID MEASURES

---

### EYE CONTACT:

Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

Flush with large quantities of water for 15 minutes.

### SKIN CONTACT:

Wash thoroughly with soap and water and seek medical attention if irritation persists. Remove contaminated clothing. Launder contaminated clothing before reuse.

### INHALATION:

For inhalation overexposure move person to fresh air. If breathing stops, apply artificial respiration and seek medical attention.

### INGESTION:

Do not induce vomiting which can cause chemical pneumonitis and pulmonary edema. Contact a physician immediately.





# MATERIAL SAFETY DATA SHEET

of California to cause cancer.

**STORAGE:**

Store in a cool dry area with ventilation suitable for storing materials shown in section 2.

Store this product indoors to protect from freezing.

Keep away from heat, sparks and flame.

Store in a cool place away from direct sunlight or any source of ignition. Do not store at temperatures above 120 degrees F.

-----  
SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION  
-----

**ENGINEERING CONTROLS:**

Sufficient ventilation, in volume and pattern, should be provided to keep air contamination below current applicable OSHA permissible exposure limit or ACGIH's TLV limit.

**RESPIRATORY PROTECTION:**

If workplace exposure limits are exceeded for any component(see section 2 for hazardous components and exposure limits), a NIOSH/OSHA approved respirator suitable for components listed is recommended.

**SKIN PROTECTION:**

Chemical resistant plastic or rubber gloves recommended for prolonged or repeated contact.

**EYE PROTECTION:**

Chemical goggles with side shields or face shield recommended if contact with the eyes is likely.

**OTHER PROTECTIVE EQUIPMENT:**

Appropriate impervious clothing is recommended if prolonged or repeated contact is likely.

**HYGIENIC PRACTICES:**

Wash hands before eating or smoking. Smoke in designated areas only.

01326 100132 604 01

-----  
SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES  
-----

Vapor Pressure . . . . .	:	5585.20	mm Hg @ 20 C
Vapor Density . . . . .	:	3.70	
Boiling Range . . . . .	:	Lower - 1.0 °F	
		Higher - 279.0 °F	
Specific Gravity . . . . .	:	.691	
Formula Weight per Volume . . . . .	:	5.7520	LB/GL
VOC (Calculated, LB/GAL) . . . . .	:	4.572	
VOC (Calculated, GM/L). . . . .	:	547.86	
Percent Volatile by Weight. . . . .	:	79.4495	
Percent Volatile by Volume . . . . .	:	84.2748	
Evaporation Rate . . . . .	:	4.600	(n-Butyl Acetate = 1)



# MATERIAL SAFETY DATA SHEET

Viscosity . . . . . : -N/A

-----  
SECTION 10 - STABILITY AND REACTIVITY  
-----

CONDITIONS TO AVOID:

Avoid contact with heat, sparks, and open flame.  
Product may explode if heated. Keep cool, avoid exposure to heat.

INCOMPATIBILITIES:

Strong oxidizing agents.

DECOMPOSITION:

Thermal decomposition may produce carbon dioxide, carbon monoxide, and unidentifiable organic materials.

POLYMERIZATION:

No hazardous polymerization will occur under normal conditions.

STABILITY:

The product is stable under normal storage conditions.

-----  
SECTION 11 - TOXICOLOGICAL INFORMATION  
-----

No specific information is available. Please refer to Section 2 and 3 for available information on exposure limits and hazards identification.

-----  
SECTION 12 - ECOLOGICAL INFORMATION  
-----

No specific ecological information is available for this product.

-----  
SECTION 13 - DISPOSAL CONSIDERATIONS  
-----

WASTE DISPOSAL:

Place in closed containers. Dispose of product in accordance with local, county, state, and federal regulations.

01326 100132 604 01

-----  
SECTION 14 - TRANSPORT INFORMATION  
-----

Ground shipment of limited or excepted quantities of aerosols or liquid paint in containers of 1 quart or less:

CONSUMER COMMODITY, ORM-D

Ground shipment of liquid paint in containers more than 1 quart:

PAINT, FLAMMABLE LIQUID, UN1263, CLASS 3, GROUP II  
(Regulatory sources: DOT 49CFR 172.101)

Air shipment of limited or excepted quantities of aerosols or liquid paint in containers of 1 quart or less:

CONSUMER COMMODITY, ID 8000, CLASS 9 MISCELLANEOUS LABEL  
(Regulatory sources: ATAI Quantity Exemptions - Table 2.8.4, 2.7.A,



# MATERIAL SAFETY DATA SHEET

2.7.5, Packaging Instruction: 910)

OR

AEROSOLS, FLAMMABLE, UN1950, CLASS 2.1 LABEL  
(Regulatory sources: ATAI Quantity Exemptions - Table 2.8.1, 2.8.4,  
Packaging Instruction: Y203)

SECTION 15 - REGULATORY INFORMATION

SARA 313 INFORMATION:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

ETHYLBENZENE

CAS# 100-41-4 PCT BY WT: 3.7880

N-HEXANE

CAS# 110-54-3 PCT BY WT: 10.2080

XYLENE

CAS# 1330-20-7 PCT BY WT: 20.7650

METHYL ETHYL KETONE

CAS# 78-93-3 PCT BY WT: 1.1610

FEDERAL REGULATIONS:

TOXIC SUBSTANCES CONTROL ACT: The chemical substances in this product are listed on the TSCA Section 8 inventory.

STATE REGULATIONS:

NEW JERSEY RIGHT-TO-KNOW

No non-hazardous ingredients are among the top five ingredients

01326 100132 604 01

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3 %

----- CHEMICAL NAME ----- CAS NUMBER

INTERNATIONAL REGULATIONS:

CANADA: The chemical substances in this product are listed on the Canadian Domestic Substances List.

SECTION 16 - OTHER INFORMATION

The information contained on this MSDS is believed to be reliable and accurate. Due to the changing nature of government information, it is





# MATERIAL SAFETY DATA SHEET

PAGE 17

impossible to guarantee the accuracy of the information contained herein. Since the conditions of handling and use are beyond our control, we make no guarantee of results and assume no liability for damages incurred by the use of this material. This information should not be regarded as legal advice or regulation. It is the responsibility of the user to comply with all Federal, State, and Local laws and regulations. For questions relating to specific aspects of the requirements and regulations consult the proper regulatory agency.

**HMIS RATINGS:**

HEALTH: 2\*    FLAMMABILITY: 4    REACTIVITY: 0    PERSONAL PROTECTION: G